

BLANK PAGE




Indian Standard SPECIFICATION FOR MAGNESITE FOR CHEMICAL INDUSTRY (First Revision)

UDC 622.368.2



© Copyright 1980

INDIAN STANDARDS INSTITUTION MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG NEW DELHI 110002



Indian Standard SPECIFICATION FOR MAGNESITE FOR CHEMICAL INDUSTRY

(First Revision)

Inorganic Chemicals (Miscellaneous) Sectional Committee, CDC 3

Chairman

Representing

DR M. S. VAIDYA

Dharamsi Morarji Chemical Co Ltd. Bombay

Members

SHRI H. T. KAPADIA (Alternate to

Dr M. S. VAIDYA)

SHRI B. N. BHATTACHARYYA

SHRI A. K. BOSE

Geological Survey of India, Calcutta

Directorate General of Technical Development. New Delhi

SHRI R. C. BHATTACHARYA (Alternate)

SHRI S. K. CHAKRABORTY

Development Commissioner, Small Scale Industries, New Delhi

SHRI S. S. HONAVAR Italab Private Ltd. Bombay

SHRI J. C. DEY (Alternate I)

SHRI M. V. DABHOLKAL (Alternate II)

SHRI H. H. KAVARANA Sarabhai M. Chemicals Ltd. Vadodara

SHRI J. K. PATWA (Alternate) SHRI R. PRABHAKAR

Tata Chemicals Ltd, Bombay

SHRI N. B. PATEL (Alternate) SHRI A. K. RAO

D.C.M. Chemical Works, New Delhi

SHRI D. V. N. SHASTRY (Alternate) SHRI B. K. SACHAR

Ministry of Defence (R&D)

SHRI A. D. GUPTA (Alternate)

DR E. R. SAXENA Regional Research Laboratory (CSIR), Hyderabad DR MD ZAFAR JAMIL (Alternate)

SHRI D. C. SHAH SHRI H. C. SHAH

Kesar Sugar Works Ltd. Bombay Golden Chemicals Pvt Ltd. Bombay

SHRI L. H. THAKKAR (Alternate)

SHRI Y. V. SHETTY

Indian Oil Corporation Ltd (Refineries and Pipelines Division), New Delhi

SHRI S. B. SHUKLA

Basic Chemicals, Pharmaceuticals and Soaps Export

Promotion Council, Bombay

(Continued on page 2)

© Copyright 1980

INDIAN STANDARDS INSTITUTION

This publication is protected under the Indian Copyright Act (XIV of 1957) and reproduction in whole or in part by any means except with written permission of the publisher shall be deemed to be an infringement of copyright under the said Act.

IS: 3607 - 1979

(Continued from page 1)

Members

Representing

Dr V. SRINIVASAN DR J. V. VORA (Alternate) Glaxo Laboratories (India) Ltd. Bombay

SHRI S. SUBBIAH

Directorate General of Supplies & Disposals. New Delhi

SHRI N. G. S. IYER (Alternate)

DR SURJIT SINGH

Ministry of Defence (DGI)

SHRI J. A. ASTHAPATRE (Alternate) SHRI N. C. THAKKAR

Indian Chemical Manufacturers' Association.

Calcutta

DR G. M. SAXENA, Director (Chem) Director General, ISI (Ex-officio Member)

Secretary

SHRI N. K. SHARMA Deputy Director (Chem), ISI

Minerals for Chemical and Allied Industries Subcommittee, CDC 3:17

Convener

SHRI B. N. BHATTACHARYYA

Geological Survey of India, Calcutta

Members

SHRI J. A. ASTHAPUTRE

Ministry of Defence (DGI)

Dr S. N. BHATTACHARYA

SHRI K. P. MAJUMDAR (Alternate)

Oil & Natural Gas Commission, Dehra Dun

SHRI H. K. CHAKRABORTY

National Metallurgical Laboratory Jamshedpur

SHRI K. A. CHINOY

English Indian Clays Ltd, Trivandrum

CONTROLLER

Indian Bureau of Mines, Nagpur

SHRI A. S. GOPALACHARI (Alternate) SHRI A. K. MISSER

Associated Cement Companies Ltd. Bombay

Shri J. V. Joshi (Alternate)

SHRI N. B. PATEL

Tata Chemicals Ltd, Bombay

SHRI V. R. V. RAGHAVAN (Alternate)

DR P. K. RAO

Regional Research Laboratory (CSIR), Bhubaneswar

SHRI P. K. SAHU (Alternate)

SHRI C. K. SHAH

Gujarat Mineral Development Corporation Ltd. Ahmadabad

SHRI S. V. JHALA (Alternate)

SHRI V. SHIVKUMAR

SHRI P. C. THAKKAR

Grindwell Norton Ltd, Bangalore

Indian Chemical Manufacturers' Association. Calcutta

SHRI B. K. VAHI (Alternate)

SHRI S. A. TRIVEDI

Navin Fluorine Industries, Bombay

SHRI J. N. PAREKH (Alternate)

Indian Standard SPECIFICATION FOR MAGNESITE FOR CHEMICAL INDUSTRY

(First Revision)

O. FOREWORD

- 0.1 This Indian Standard (First Revision) was adopted by the Indian Standards Institution on 3 August 1979, after the draft finalized by the Inorganic Chemicals (Miscellaneous) Sectional Committee had been approved by the Chemical Division Council.
- 0.2 Magnesite occurs in two forms, namely, crystalline and amorphous. Amorphous form is commonly found in India. It is white in colour and breaks with conchoidal fracture. India has extensive deposits of high grade magnesite located in Mysore, Salem district of Tamil Nadu and in Almora district of Uttar Pradesh.
- 0.3 Magnesite is used in the manufacture of dead burnt magnesium oxide, epsom salts and caustic magnesia for magnesium oxychloride compositions, and in rubber and other chemical industries.
- 0.4 This standard was first published in 1966. The standard is now being revised in the light of experience gained during these years. In this revision the limit of iron oxide is being lowered from 1.0 to 0.4. Changes are also made in the method of test for calcium.
- 0.5 For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test or analysis, shall be rounded off in accordance with IS:2-1960*. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

1. SCOPE

1.1 This standard prescribes the requirements and the methods of sampling and test for magnesite used in chemical industry.

^{*}Rules for rounding off numerical values (revised).

2. REQUIREMENTS

- 2.1 Description The material shall be in the form of white lumps, and free from dirt and other foreign matter.
- 2.2 The material shall comply with the requirements given in Table 1, when tested according to the methods prescribed in Appendix A of this standard and IS:1760-1962*. Reference to the relevant test methods is given in col 4 and 5 of the table.

TABLE 1 REQUIREMENTS FOR MAGNESITE FOR CHEMICAL INDUSTRY

SL	Characteristic R	EQUIREMENT	Метнор о	of Tests, Ref to
No.			Appendix	Cl No. in IS:1760-1962*
(1)	(2)	(3)	(4)	(5)
i)	Loss on ignition, percent by mass, Min	48.0	_	5
ii)	Silica (as SiO ₂), percent by mass, Max	2.0	_	6
iii)	Alumina (as Al ₂ O ₃), percent by mass, Max	0.3	****	7
iv)	Iron oxide (as Fe ₂ O ₃), percent by mass, Max	0·4	_	8
v)	Magnesium (as MgO), percent by mass, Min	45.0	_	11
vi)	Calcium (as CaO), percent by mass, Max	1.0	Α	

^{*}Methods of chemical analysis of limestone, dolomite and allied materials.

3. PACKING AND MARKING

- 3.1 Packing Unless otherwise agreed between the purchaser and the supplier, the material shall be supplied in open wagons.
- 3.2 Marking A good sized metallic or cardboard label bearing the following information with suitable paint or ink shall be conspicuously displayed on the carrier and also placed inside:
 - a) Name of the material;
 - b) Name of the supplier and the recognized trade-mark, if any;
 - c) Gross and net mass;
 - d) Date of supply; and
 - e) Batch number.

^{*}Methods of chemical analysis of limestone, dolomite and allied materials.

3.2.1 The material may also be marked with the ISI Certification Mark.

Note—The use of the ISI Certification Mark is governed by the provisions of the Indian Standards Institution (Certification Marks) Act and the Rules and Regulations made thereunder. The ISI Mark on products covered by an Indian Standard conveys the assurance that they have been produced to comply with the requirements of that standard under a well-defined system of inspection, testing and quality control which is devised and supervised by ISI and operated by the producer. ISI marked products are also continuously checked by ISI for conformity to that standard as a further safeguard. Details of conditions under which a licence for the use of the ISI Certification Mark may be granted to manufacturers or processors, may be obtained from the Indian Standards Institution.

4. SAMPLING

- **4.1 Preparation of Test Samples** Representative samples of the material shall be drawn as prescribed in IS: 2109-1962*.
- **4.2 Number of Tests** Tests for the determination of magnesium, silica and loss on ignition shall be conducted on each of the individual samples. Tests for the determination of the remaining characteristics shall be performed on the composite sample.
- 4.3 Criteria for Conformity The lot shall be declared as conforming to the requirements of this specification if the conditions given in 4.3.1 and 4.3.2 are satisfied.
- **4.3.1** For each of the characteristics tested on individual samples (see **4.2**), all the test results satisfy the relevant requirements given in the specification.
- **4.3.2** All the test results on the composite sample satisfy relevant requirements given in the specification.

APPENDIX A

[Clause 2.2 and Table 1, Item (vi)]

DETERMINATION OF CALCIUM IN MAGNESITE

A-0. GENERAL

A-0.1 Calcium may be determined by two methods, namely, EDTA titration method and phosphate method. For routine analysis, the EDTA method prescribed here shall be followed; in case of dispute, phosphate method as prescribed in 11 of IS:1760-1962† shall be followed.

^{*}Methods of sampling dolomite, limestone and other allied materials.

[†]Specification for dolomite, limestone and allied materials.

IS: 3607 - 1979

A-0.2 Outline of the Method — The sample is treated with hydrochloric acid and insoluble matter is removed by filtration. Triethanolamine is added to form a complex with the R_2O_3 group and a known volume of standard EDTA is added. This volume is sufficient to complex all the calcium and the excess complexes its equivalent amount of magnesium; the remainder of the magnesium is then precipitated with sodium hydroxide. The magnesium EDTA complex is titrated with standard calcium solution using Patton and Reeder's indicator.

A-1. OUALITY OF REAGENTS

A-1.1 Unless specified otherwise, pure chemicals and distilled water (see IS: 1070-1977*) shall be employed in tests.

Note — 'Pure chemicals' shall mean chemicals that do not contain impurities which affect the results of analysis.

A-2. REAGENTS

- A-2.1 Concentrated Hydrochloric Acid see IS: 265-1976†.
- A-2.2 Magnesium Sulphate Solution Dissolve 25 g of magnesium sulphate (MgSO_{4.7}H₂O) in water, filter and dilute to 500 ml.
- A-2.3 Sodium Hydroxide Solution approximately 4 N.
- A-2.4 Concentrated Nitric Acid see IS:264-1976‡.
- A-2.5 Triethanolamine 1:1 (v/v).
- A-2.6 Standard Calcium Chloride Solution 0.05 M. Dissolve 5.005 g of dried calcium carbonate in a slight excess of dilute hydrochloric acid (1:3). Boil to expel carbon dioxide, cool and dilute to 1 litre.
- A-2.7 Standard Ethylenediamine Tetra-acetate (EDTA) Solution Approximately 0.05 M. Dissolve 18.65 g of disodium tetra-acetate dihydrate in warm water, filter, cool and dilute to 1 litre.
- A-2.8 Pattern and Reeder's Indicator Intimately mix by grinding, about 0.1 g of Patton and Reeder's indicator with about 50 g of anhydrous potassium sulphate. Store in a well-stoppered bottle protected from light.
- A-2.9 Ascorbic Acid solid.

A-3. PROCEDURE

A-3.1 Standardization of EDTA Solution — Pipette 25 ml of the EDTA solution into a 500-ml conical flask and add 50 ml of magnesium sulphate

^{*}Specification for water for general laboratory use (second revision).

[†]Specification for hydrochloric acid (second revision).

[‡]Specification for nitric acid (second revision).

solution, dilute to about 250 ml and shake well. Then add 25 ml of sodium hydroxide solution followed by 0.25 g of the indicator and again shake well. Immediately titrate with the calcium chloride solution till colour changes from blue to wine red. EDTA solution shall be standardized only when required.

A-3.2 Weigh accurately about 1 g of the dried and finely ground sample into a 250-ml beaker. Add 5 ml of water and 10 ml of concentrated hydrochloric acid, cover the beaker with a watch-glass and boil until all soluble matter dissolves. Add a drop of nitric acid and boil off the fumes of nitrous oxide. Rinse any deposit from the underside of the watch-glass into the beaker. Dilute to about 100 ml, filter and wash, collecting the filtrate and washings in a 500-ml conical flask. Cool, add 5 ml of triethanolamine, and pipette into the solution 25 ml of EDTA solution, then add sodium hydroxide solution, drop by drop with shaking until a slight permanent precipitate remains. Dilute to about 250 ml, add 25 ml of the sodium hydroxide solution, add about 1 g of the ascorbic acid and about 0.2 g of the indicator. Titrate immediately with the standard calcium chloride solution exactly as given in A-3.1.

A-4. CALCULATION

A-4.1 If 25 ml of the EDTA solution is equivalent to a ml of calcium chloride solution and b ml of the latter solution is used in the back titration, then the percentage of calcium oxide in the dry, unignited sample is 0.2804 (a-b)/m, where m is the mass in g of the sample taken.

INTERNATIONAL SYSTEM OF UNITS (SI UNITS)

Base Units

Quantity	Unit	Symbol
Length	metre	m
Mass	kilogram	kg
Time	second	s
Electric current	ampere	Α
Thermodynamic temperature	kelvin	K
Luminous intensity	candela	cd
Amount of substance	mole	mol

Supplementary Units

Quantity	Unit	Symbol
Plane angle	radian	rad
Solid angle	steradian	sr

Derived Units

Quantity	Unit	Symbol	Definition
Force	newton	N	$1 N=1 kg. m/s^2$
Energy	joule	J	1 J=1 N.m
Power	watt	W	1 W=1 J/s
Flux	weber	Wb	1 Wb = 1 V.s
Flux density	tesla	T	1 $T=1 \text{ Wb/m}^2$
Frequency	hertz	Hz	1 Hz=1 c/s (s^{-1})
Electric conductance	siemens	S	1 S=1 A/V
Electromotive force	volt	v	1 V=1 W/A
Pressure, stress	pascal	Pa	$1 Pa=1 N/m^2$

PUBLICATIONS OF INDIAN STANDARDS INSTITUTION

Over 10 000 Indian Standards covering various subjects have been issued so far. Of these, the standards belonging to the Chemical Group fall under the following categories:

Acids	Linters and allied products
Adhesives	Lubricants and related products
Alcohols and allied products	Oll pastes
Alkalis	Oils & fats, oleaginous seeds and
Brushware	fruits
Ceramicware, enamelware and labora- tory porcelain	Painters' materials (miscellaneous) Paper and its products
Chemical hazards and safety	Paper and pulp board packaging
Chemicals, inorganic (miscellaneous)	materials
Chemicals, organic (miscellaneous) Coal and coke	Perfumery materials, natural and synthetic
Coal carbonization products	Petroleum and petroleum products
Coated fabrics	Photographic chemicals
Cosmetics and toilet goods	Pigments and extenders
Dental materials	Plastics
Drying oils	Polishes
Dye intermediates	Printing lnks
Electroplating chemicals	Ready mixed paints and enamels
Explosive and pyrotechnic materials	Rubber and rubber products
Fertilizers	Soaps and other surface active
Fillers, stoppers and puttles	agents
Footwear	- Tanning materials and allied
Glass and glassware	products
Industrial gases	Thermal insulation materials
Inks and allied products	Thinners and solvents
Laboratory glassware, thermometers	Varnishes and lacquers
and related apparatus	Water and water treatment
Lac and lac products	Water based paints
Leather, leather goods and leather dressings	Unclassified
OTHER BURL	ICATIONS

OTHER PUBLICATIONS

ISI Bulletin (Published Eve	ry Mon	th)				
Single Copy		The state of the		-	200	Rs 4:00
Annual Subscription	in.			1000	1 (24)	Rs 36-00
Standards : Monthly Addition	ns					
		444	(44)	407	1995	Re 0-30
	210	100	****	200	16 1000	Rs 3.00
Annual Reports (from 194	8-49 On	wards)		***	Rs	2.00 to 7.00
ISI Handbook, 1978		***			100	Rs 60.00

INDIAN STANDARDS INSTITUTION

Manak Bhavan, 9 Bahadur Shah Zafar Marg. NEW DELHI 110002

Telephones : 26 60 21, 27 01 31	Telegrams: Mana	ksanstha
Ragional Offices:	1	elephone
Western : Novelty Chambers, Grant Road	BOMBAY 400007	37 97 29
Eastern : 5 Chowringhee Approach	CALCUTTA 700072	23-08 02
Southern : C.I.T. Campus, Adyar	MADRAS 600020	41 24 42
Branch Offices:		
'Pushpak', Nurmohamed Shaikh Marg, Khanpur	AHMADABAD 380001	2 03 91
F' Block, Unity Bldg, Narasimharaja Square	BANGALORE 560002	2 76 49
Gangotri Complex, Bhadbhada Road, T.T.Nagar	BHOPAL 462003	6 27 16
22E Kalpana Area	BHUBANESHWAR 751014	5 36 27
Ahimsa Bldg, SCO 82-83, Sector 17C	CHANDIGARH 160017	2 83 20
5-8-56C L. N. Gupta Marg	HYDERABAD 500001	22 10 83
D-277 Todarmal Marg, Banipark	JAIPUR 302006	6 98 32
117/418 B Sarvodaya Nagar	KANPUR 208005	8 12 72
Patliputra Industrial Estate	PATNA 800013	6 28 08
Hantex Bldg (2nd Floor), Rly Station Road	TRIVANDRUM 695001	32 27